

BKR 5000 P25 Portable Radio Specification Sheet



Public Safety Communications

The **BKR** Series Portable Radio offers exceptional performance in a lightweight form factor, incorporating industry-leading RF and electrical specifications in a rugged, submersible housing.

- ✓ Large, Bright, Color Display and Top Display
- ✓ Enhanced Noise Cancellation
- ✓ 3 Programmable Side Buttons
- ✓ Loud, Crisp Audio
- ✓ P25 Trunking Option
- ✓ TDMA Phase II
- ✓ IP68 Water and Dust Protection
- ✓ Internal GPS and Bluetooth Hardware
- ✓ USB PC Programmable
- ✓ AES256, AES128, DES-OFB/CFB/XL
- ✓ MIL-STD 810 C/D/E/F/G
- ✓ Advanced System Key

BKR 5000 P25 Portable Radio

Color Display	6-line display 3 customizable display lines of 16 characters 2 lines of status icons 1 line of soft-keys
Keypad	Back-lit with 4 customizable soft-keys
Channel Capacity Memory	5000
VHF	BKR 5000-V
Buttons and Switches	Oversized PTT, On/Off Volume control, orange emergency button, 16 position rotary switch, 4 positions concentric zone switch, 3 programmable side buttons, programmable collar switch



Transmitter Certifications

VHF (FCC/IC)	FCC ID: K95BKR5000-V, IC ID: 2116A-BKR5000V
---------------------	---

FCC Emission Designators

FCC Emission Designators	11K0F3E, 8K10F1D, 8K10F1E, 8K10F1W
---------------------------------	------------------------------------

Power Supply

Power Supply	Rechargeable Li-Ion or AA-Alkaline Battery Pack
---------------------	---



- **Exceptional Battery Life**
Up to 12 hours with standard capacity.
- **Enhanced Voice Quality**
The BKR Series radio uses the Third Generation Enhanced IMBE P25 dual-rate Vocoder (AMBE+2 V1.80) for robust performance in noisy environments.
- **6 Line Display**
2 Status Icons, 3 customizable display lines of 16 characters, and 1 line of soft-keys.
- **Environmental Reliability**
Designed and tested to MIL-STD-810 and IP-68 rated.
- **DHS P25 CAP Approved**
DHS P25 Compliance Assessment Program Tested and Approved Public Safety Grade (TIA Class A).
- **Robust Receiver**
Improved range and less susceptibility to interference.
- **Simulcast Operation**
C4FM and CQPSK modes for robust performance in simulcast (including LSM) systems.
- **Conventional Signaling**
Analog MDC-1200 and Digital APCO P25 for conventional operation.
- **Internal Bluetooth Hardware**
BK Technologies Bluetooth is a programmable option for wireless accessory connectivity. (Release date TBD).
- **Scan Modes**
Dual priority scan, trunked priority scan, dual-mode scan, channel, zone and vote scan.
- **Encryption**
The BKR Series radios support AES256, AES128, DES-OFB/CFB/XL encryption and is compatible with Motorola's ADP.
- **Multi-key/Multi-Algorithm**
Multi-Key/Multi-Algorithm Encryption.
- **Over-the-Air Rekey (OTAR)**
- **Encryption Key Fill**
TIA-102AACD compliant and interoperable with commercially available key fill devices.
- **P25 9600 Baud Trunking**
The BKR Series radio operates on 9600 baud P25 Compliant Trunking Systems and has been P25 Compliance Assessment Program (P25CAP) tested and proven interoperable.
- **OTAP**
BKR Series radios support Over-the-Air Programming (OTAP) for operational efficiency.
- **TDMA Phase 2**
BKR Series VHF is P25 Phase 2 (TDMA) capable supporting double the voice capacity of Phase 1 trunking systems.
- **Radio Authentication**
P25 Radio Authentication per TIA-102-AAACE-A is supported.
- **Integrated GPS/Location Services**
P25 Location Services per TIA-102-BAJB are supported, Tier I Conventional, Tier II Trunking.

Portable Radio Features

The BKR platform meets today's demanding mission-critical voice requirements and is future-ready to expand with changing standards and mission requirements.

- **BKR0582** OTAP, Trunking
- **BKR0570** OTAR (Trunking & Conventional)
- **BKR0579** P25 FDMA Trunking
- **BKR0593** P25 TDMA Trunking
- **BKR5780** Radio Authentication
- **BKR0574** DES & AES FIPS140-2 Level 2 Encryption w/ "tamper proof"
- **BKR0581** Multi-cast Vote Scan Plus

Receiver Minimum Performance Specifications

		VHF
Frequency Range		136-174 MHz
Channel Spacing		25/12.5 kHz
Max Frequency Separation		Full Band
Rated Audio Output Power		3 Watts
Analog Sensitivity	12dB SINAD	0.2 μ V / -121.0 dBm
Digital Sensitivity	1%BER	0.277 μ V / -118.15 dBm
	5%BER	0.2 μ V / -121.0 dBm
Selectivity	25 kHz	\geq 80 dB
	12.5 kHz	\geq 70 dB
Intermodulation		\geq 78 dB
Spurious Rejection		\geq 80 dB
FM Hum and Noise	25 kHz	\geq 50 dB
	12.5 kHz	\geq 44 dB
Audio Distortion		2%


Transmitter Minimum Performance Specifications

		VHF
Frequency Range		136-174 MHz
Channel Spacing		25/12.5 kHz
Max Frequency Separation		Full Band
Rated RF Output Power		1- 6 Watts
Frequency Stability (-30°C to +60°C, +25°C Reference)		\pm 1 ppm
Modulation Limiting		\pm 5/2.5 kHz
Emissions (Conducted and Radiated)		\geq 75 dB
Audio Response		+1, -3 dB
FM Hum and Noise	25 kHz	\geq 50 dB
	12.5 kHz	\geq 44 dB
Audio Distortion		3%

BKR Series Batteries

Battery Capacity/Type	Dimensions (HxWxD)	Part Number	Capacity
Li-Ion Smart 4900 mAh	3.0 x 2.3 x 1.8	BKR0101	4900 mAh > 12 Hours
AA Clamshell	5.2 x 2.3 x 2.2	BKR0120	12 cells > 12 Hours

Removing the Battery




1. Push in the release tabs on each side of the battery.
2. Pull the battery downwards away from the radio.

NOTE: All information programmed into the radio is maintained even when the battery pack is removed.

The **BKR 5000** display can be programmed for a variety of options and functionality. Check with your Sales Representative or Communications Officer for information on the programmed functions of your radio.

NOTE: The **BKR 5000** display can be programmed to display different information when a trunking or conventional channel is selected.

Radio Controls



BKR 5000 Portable Military Standards C,D,E, F, & G

	MIL-STD 810G	
	Method	Proc. / Cat .
Low Pressure	500.5	I, II
High temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	1-D
Contamination by Fluids	504.1	II
Solar Radiation	505.5	I
Rain/Blown Rain	506.5	I
Humidity	507.5	II
Salt Fog	509.5	I
Dust and Sand	510.5	I, II
Immersion	512.5	I
Vibration	514.6	I/4
Shock	516.6	I, IV, VI

Encryption

BKR 5000 Portable 5000 Channel Encryption Capabilities

Supported Algorithms	AES-256, AES-128, DES-OFB, DES-CFB, ADP
Encryption Keys	1024 Storage Location Number (SLN)/ Common Key Reference (CKR)
Frame Re-sync Interval	P25 Common Air Interface 360 mS
Keyloading	IAW TIA-102_AACD (KVL-3000/ 4000}
Synchronization	OFB- Output Feedback or CFB- Cyber Feedback
Type	Digital Encryption
Key Storage	Programmable Volatile / Non-Volatile
Key Erasure	Keyboard Command and KMF
Standards	FIPS-140-2 Level 2 FIPS 197

Dimensions with Battery

	Inches	Millimeters
Width	2.3	59.6
Depth	1.8	45.7
Height	6.5	166.2
Weight	Pounds	Grams
Weight (with battery)	1.34 lbs	608g
Weight (w/o battery)	0.89 lb	404g

Other Certifications

P25 Compliance Assessment (P25CAP) Performance	Trunked and Conventional Performance Class A
P25 Compliance Assessment (P25CAP) Interoperability	Motorola, L3Harris, Tait/Zetron

KNG/BKR SERIES PORTABLE RADIO STANDARD FEATURES



STANDARD FEATURES	KNG2 PORTABLE	BKR-5000
Conventional Analog	✓	✓
APCO P25 Digital	✓	✓
TDMA	✓	✓
VHF (136-174MHz)	✓	✓
UHF (440-520MHz)	✓	✓
7/800 (763-870MHz)	✓	✓
5000 Channels	✓	✓
Birdie Free	✓	✓
Alphanumeric Keypad	✓	✓
Tier 2 (No Keypad) Avail.	✓	✓
Programmable Front Buttons	✓	✓
3 Side Programmable Buttons	✓	✓
Programmable Toggle Switches	✓	✓
Priority Scan	✓	✓
Dual Mode Scan	✓	✓
Channel Scan	✓	✓
Group Scan	✓	✓
Emergency Signaling	✓	✓
NIST FIPS-140-2 Certified	✓	✓
MIL-SPEC C/D/E/F/G	✓	✓
USB Programmable	✓	✓
Talk Around	✓	✓
Text Messaging	✓	✓
Color LCD Display	✓	✓
Dual Microphones	✓	✓
Noise Cancellation	✓	✓
Top LCD Display	✓	✓
Four Position (A, B, C, D) Switch	✓	✓

KNG/BKR SERIES PORTABLE RADIO OPTIONS



AVAILABLE OPTIONS	KNG2 PORTABLE	BKR-5000
OTAP	✓	✓
OTAR	✓	✓
Phase II TDMA	✓	✓
DES/AES Encryption	✓	✓
FIPS140 Level 2 Encryption	✓	✓
Multi-cast Vote Scan	✓	✓
P25 Trunking	✓	✓
Radio Authentication	✓	✓
Site Authentication	✓	✓
GPS	✓	✓

